



TMM5100/470 PINSTAMP® Multiple Pin Marking System

Mark up to six characters-per-second with the **PINSTAMP®** TMM5100/470 Multiple Pin Marking System. Its lightweight, compact design and minimal footprint are ideal for hand-held, stand-alone or completely integrated, factory automated operations. A variety of pin sizes/configurations are available to mark character heights from .04" - .63" (1mm - 16mm) on a wide range of materials.



FEATURES

- High speed — up to six pins marking simultaneously
- Marking windows up to 0.625" x 4.5" (16mm x 114mm)
- Marks a wide range of materials from soft plastics to hardened steel — up to Rc60
- Available with a variety of marking pin cartridge configurations for the optimal combination of character size, marking depth, marking window size and cycle time
- Compact, rugged X/Y positioning mechanism
- The right choice for many VIN (Vehicle Identification Number) Marking Applications
- Self-contained, state-of-the-art TMC470 controller features two serial ports, USB and Ethernet ports
- Automatically generates serial numbers, time, date and shift codes
- Stores up to 400 marking patterns
- Easily interfaced to PLCs (Programmable Logic Controllers) and Host Computers
- Pin travel accommodates surface irregularities to 0.25" (6mm)

OPTIONAL ACCESSORIES

- Panel-mount and IP/NEMA-Rated controller options
- Marking head support tooling and balancers
- Logo/Font design software package for design of custom fonts or logos
- PC-Based Upgrade Utility available FREE from www.telesis.com for easy software upgrade
- PC-Based Pattern Back-up Utility available FREE from www.telesis.com



Compact Self-Contained
TMC470 Controller — no PC required.



QR Code Web Page Product Link

DATA MATRIX™ 2-D Code Marking Capability
Meets all Department of Defense UID Requirements
and other industry standards