

Mark a **WIDE RANGE** of **INDUSTRIAL** and **CONSUMER PRODUCTS** with the  
**ProScript**® **SABRE**™  
**CO<sub>2</sub> LASER** by **TELESIS**

Available in 10, 30 and 50 watt configurations. SABRE can mark softer substrates like wood, glass, plexiglass, quartz, ceramics, even fabrics and other organic materials.

**FEATURES:**

- Unique, Single Rail Design for Easy Alignment and Increased Power
- Compact Marking Head with Two-Piece Cover and Simple Mounting System
- Hand Held Pendant for Convenient Remote Operation
- Co-Axial Red Pointer Diode for Pin Point Marking Alignment
- **TELESIS DESIGNED** Fixed Beam Expansion and Shutter Assembly
- **DETACHABLE 6'** Laser End Umbilical Cable
- Air-cooled - No External DI Water Needed
- **CDRH Compliant** Keyswitch, E-Stop Manual Safety Shutter and Emission Light



Small Laser Controller and Unique, Dual Function Control Pendant

All Marking Head Components and Assembly Warranted for One Year

**OPTIONAL 90, 180 and 270 degree Galvo Rotation** allows Vertical and Horizontal firing



**LENS CONFIGURATIONS AVAILABLE:**

Focal Length	Marking Field	Work Clearance	
100mm	70mm x 70mm	(2.7" x 2.7")	81mm (3.18")
150mm	100mm x 100mm	(4.0" x 4.0")	131mm (5.15")
200mm	140mm x 140mm	(5.5" x 5.5")	184mm (7.24")
* 250mm	170mm x 170mm	(6.6" x 6.6")	233mm (9.17")
* 300mm	205mm x 205mm	(8.0" x 8.0")	283mm (11.14")
* 360mm	250mm x 250mm	(9.8" x 9.8")	351mm (13.8")

\* Application dependent



